

AFRL-ML-TY-TR-2002-4604



**F100 ENGINE NACELLE FIRE FIGHTING TEST
MOCKUP DRAWINGS**

JULY 2002

Approved for Public Release; Distribution Unlimited

**MATERIALS & MANUFACTURING DIRECTORATE
AIR FORCE RESEARCH LABORATORY
AIRBASE TECHNOLOGIES DIVISION
139 BARNES DRIVE, STE 2
TYNDALL AFB FL 32403-5323**

NOTICES


THIS REPORT WAS PREPARED BY THE AIR FORCE RESEARCH LABORATORY (AFRL) AIRBASE TECHNOLOGIES DIVISION, TYNDALL AIR FORCE BASE, FLORIDA 32403.

USING GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA INCLUDED IN THIS DOCUMENT FOR ANY PURPOSE OTHER THAN GOVERNMENT PROCUREMENT DOES NOT IN ANY WAY OBLIGATE THE US GOVERNMENT. THE FACT THAT THE GOVERNMENT FORMULATED OR SUPPLIED THE DRAWINGS, SPECIFICATIONS, OR OTHER DATA DOES NOT LICENSE THE HOLDER OR ANY OTHER PERSON OR CORPORATION; OR CONVEY ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT MAY RELATE TO THEM.


THIS REPORT HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION.



DOUGLAS DIERDORF
Project Officer
AFRL/MLQD



RICHARD N. VICKERS, DR-IV
Chief, Deployed Base Systems Branch
AFRL/MLQD



DONALD R. HUCKLE, JR., Colonel, USAF
Chief, Airbase Technologies Division

REPORT DOCUMENTATION PAGE			<i>Form Approved OMB No. 0704-0188</i>
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.			
1. AGENCY USE ONLY (<i>Leave blank</i>)	2. REPORT DATE JULY 2002	3. REPORT TYPE AND DATES COVERED FINAL REPORT JULY 2002	
4. TITLE AND SUBTITLE F100 ENGINE NACELLE FIRE FIGHTING TEST MOCKUP DRAWINGS		5. FUNDING NUMBERS F08637-98-C-6001	
6. AUTHORS			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) AIR FORCE RESEARCH LABORATORY (AFRL/MLQD) MATERIALS AND MANUFACTURING DIRECTORATE AIRBASE TECHNOLOGIES DIVISION TYNDALL AFB, FL 32403-5323		8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSORING/MONITORING AGENCY REPORT NUMBER AFRL-ML-TY-TR-2002-4604	
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION/AVAILABILITY STATEMENT Distribution Unlimited; Approved for Public Release		12b. DISTRIBUTION CODE A	
13. ABSTRACT (<i>Maximum 200 words</i>) This report contains drawings and a bill of materials for the construction of an F100 Engine Nacelle Test Fixture and a test pad. The test fixture is designed to produce three-dimensional, or running fuel, fires to simulate an aircraft engine fire. It is utilized for evaluating the effect of fire fighting agents when attacking a fire from the engine intake, tailpipe or access panels. The test pad is designed to contain fuel from evaluations and regulate the ground fire size with a sloped concrete surface. This is a supporting drawing package for TR# AFRL-ML-TY-TR-02-4540, "Minimum Performance Requirement for Air Force Flightline Fire Extinguishers: Extinguishing Performance Against 3-Dimensional and Hidden Fires".			
14. SUBJECT TERMS MOCKUP, F100 ENGINE, FIRE FIGHTING		15. NUMBER OF PAGES	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Computer Generated

STANDARD FORM 298 (Rev 2-89)

Prescribed by ANSI Std Z39-18

298-102


TABLE OF CONTENTS

PREFACE	vi
F100 ENGINE NACELLE	1
1. ENGINE NACELLE TOP VIEW (INNER & OUTER BARRELS)	2
2. ENGINE NACELLE TOP VIEW (INNER BARREL ONLY)	3
3. ENGINE NACELLE SIDE VIEW	4
ENGINE NACELLE BAFFLE	5
4. ENGINE NACELLE BAFFLE	6
5. BAFFLE INSTALLED IN NACELLE	7
TEST FIXTURE STAND	8
6. TEST STAND -- SIDE VIEW	9
7. TEST STAND -- REAR VIEW	10
FUEL SUPPLY	11
8. ENGINE NACELLE FRONT VIEW W/ FUEL LINES	12
9. ENLARGED VIEW OF FUEL SUPPLY LINE VIEW FROM CENTER OF NACELLE	13
10. ENGINE NACELLE SIDE VIEW W/ FUEL LINES	14
11. ENLARGED VIEW OF FUEL NOZZLE DETAIL	15
THERMOCOUPLE LOCATION	16
12. ENGINE NACELLE REAR VIEW - THERMOCOUPLE LOCATION	17
13. TOP VIEW THERMOCOUPLE LOCATION DETAIL	18
FIRE TEST PAN	19
14. FIRE TEST PAN -- PLAN VIEW	20
15. FIRE TEST PAN -- BOTTOM VIEW	21
16. FIRE TEST PAN -- PLAN VIEW A-A	22
BILL OF MATERIALS	23

PREFACE

This report contains drawings and a bill of materials for the construction of an F100 Engine Nacelle Test Fixture and a test pad. The test fixture is designed to produce three-dimensional, or running fuel, fires to simulate an aircraft engine fire. It is utilized for evaluating the effect of fire fighting agents when attacking a fire from the engine intake, tailpipe or access panels. The test pad is designed to contain fuel from evaluations and regulate the ground fire size with a sloped concrete surface.

F100 ENGINE NACELLE FIRE FIGHTING TEST MOCKUP




F100 ENGINE NACELLE




DRAWINGS

1. ENGINE NACELLE TOP VIEW (INNER & OUTER BARRELS)
2. ENGINE NACELLE TOP VIEW (INNER BARREL ONLY)
3. ENGINE NACELLE SIDE VIEW


EACH BARREL FABRICATED SEPARATELY. COMPONENTS SINGLE VEE GROOVE WELDED TO FORM 16' TOTAL LENGTH



1. ENGINE NACELLE TOP VIEW (INNER & OUTER BARRELS)



2. ENGINE NACELLE TOP VIEW (INNER BARREL ONLY)




3. ENGINE NACELLE SIDE VIEW

ENGINE NACELLE BAFFLE



DRAWINGS


4. ENGINE NACELLE BAFFLE
5. BAFFLE INSTALLED IN NACELLE



BAFFLE ASSEMBLY SIDE VIEW

SCALE: N.T.S.

4. ENGINE NACELLE BAFFLE



BAFFLE ENLARGED
SCALENTS


5. BAFFLE INSTALLED IN NACELLE

TEST FIXTURE STAND



DRAWINGS


6. TEST STAND -- SIDE VIEW
7. TEST STAND -- REAR VIEW



SCALE: N.T.S

6. TEST STAND -- SIDE VIEW

MILD STEEL SUPPORT PIPE (TYP)



ID 2.47", OD 2.87" MILD STEEL PIPE SUPPORT FRAME
ALL CONNECTIONS SINGLE-BEVEL GROOVE WELDED

SCALE: N.T.S


7. TEST STAND -- REAR VIEW

FUEL SUPPLY




DRAWINGS

8. ENGINE NACELLE FRONT VIEW W/ FUEL LINES
9. ENLARGED VIEW OF FUEL SUPPLY LINE VIEW FROM CENTER OF NACELLE
10. ENGINE NACELLE SIDE VIEW W/ FUEL LINES
11. ENLARGED VIEW OF FUEL NOZZLE DETAIL




SCALE: N.T.S.

8. ENGINE NACELLE FRONT VIEW W/ FUEL LINES





9. ENLARGED VIEW OF FUEL SUPPLY LINE VIEW FROM CENTER OF NACELLE



SCALE: N.T.S.

10. ENGINE NACELLE SIDE VIEW W/ FUEL LINES




11. ENLARGED VIEW OF FUEL NOZZLE DETAIL

THERMOCOUPLE LOCATION




DRAWINGS

12. ENGINE NACELLE REAR VIEW - THERMOCOUPLE LOCATION
13. TOP VIEW THERMOCOUPLE LOCATION DETAIL



12. ENGINE NACELLE REAR VIEW - THERMOCOUPLE LOCATION



THERMOCOUPLE NOTES

BARE WIRE THERMOCOUPLE W/
20 GA. TYPE K -- HIGH TEMPERATURE
SILFA SILICA INSULATION

LEGEND

(TC) INDICATES THERMOCOUPLE LOCATION


13. TOP VIEW THERMOCOUPLE LOCATION DETAIL

FIRE TEST PAN




DRAWINGS


14. FIRE TEST PAN -- PLAN VIEW
15. FIRE TEST PAN -- BOTTOM VIEW
16. FIRE TEST PAN -- PLAN VIEW A-A



14. FIRE TEST PAN -- PLAN VIEW



15. FIRE TEST PAN -- BOTTOM VIEW



16. FIRE TEST PAN -- PLAN VIEW A-A

BILL OF MATERIALS

PART DESCRIPTION	QTY	Purpose
1/4 inch mild steel plate 10 foot x 10 foot	4 pcs	Fire Test Pan
6 x 4 x 1/4 inch mild steel angle iron – 20 ft. section	4 pcs	Fire Test Pan
2 x 2 x 1/4 inch mild steel square tubing – 20 ft section	3 pcs	Fire Test Pan
3000 psi concrete	5 cu. yards	Fire Test Pan
2 x 24 x 1/2 inch mild steel Plate – 20 ft section	1 pcs	Test Pan Backboard
1/4 inch mild steel plate 4 foot x 8 foot	7 pcs	Outer Barrel
1/4 inch mild steel plate 4 foot x 8 foot	6 pcs	Inner Barrel
1/4 inch stainless steel plate 4 foot x 8 foot	3 pcs	Baffle Material
4 x 1/4 inch mild steel square tubing – 1 ft	1 pcs	Ignition Port
1/2 inch mild steel plate 4 foot x 4 foot	1 pcs	4 – 2'X2' Feet
3" mild steel pipe ID 2.47", OD 2.87" – 20 ft section	7 pcs	Test Fixture Stand
3/8" Ball Valve	3 pcs	Fuel Supply
3/8" Stainless Steel Tubing	30 feet	Fuel Supply
3/8" Fulljet Maximum Free Passage Stainless Steel Spray Nozzles Type 3/8HHMFP-SS9022	3 pcs	Fuel Supply
Silfa Silica Insulated 20 ga. K-type Thermocouple wire	100 ft.	Temperature Measurements